



BALBOA
water group

distributed by Warmpac

CLIM8ZONE



SPECIFICATIONS

- Ability to heat and cool SPA water,
- Energy saving during water heating,
- Full integration with the SpaTouch3 panel,
- Unlike other SPA heat pumps, the Clim8Zone operates at very low outdoor temperatures below -20°C .



SPECIFICATIONS

PRODUCT	SPA HEAT PUMP
For a SPA	Equipped with a 3 kW heater
Heating power *	2,4 - 6,3 kW
Consumption *	0,21 - 1,12 kW
COP *	11,4 - 5,63
Heating power **	1,8 - 4,7 kW
Consumption **	0,18 - 0,89 kW
COP **	10 - 5,28
Power	230 V~/ 50 Hz
Gas	R32
Controller compatibility	SpaTouch3 - mini spa touch - TP700
Electronic board compatibility	BP20 - BP21 - BP501 - BP6 - BP2 - BP1
Fan direction	Horizontal
Acoustic power at 1 m	40 - 52 dB(A)
Fitting diameter	ø50 mm
Unit size (l*L*h)	850 * 407 * 414 mm
Net weight	54 kg
Brut weight	66 kg
Working ambient temperature range	-5°C ~ 43°C
Mode	Heating - Cooling - Auto
Warranty all parts	2 years

*Test carried out at 27°C air temperature with the same temperature and water flow rate difference obtained at 15°C.

**Test carried out at 15°C air temperature with a water inlet at 26°C and a water outlet at 28°C to define the water flow rate, heating capacity and consumption, according to FPP standards.

THE CLIM8ZONE OFFERS USERS 3 OPTIONS FOR HEATING AND COOLING OF THE SPA WATER



Heating and Cooling mode

Heats and cools the spa water according to the user-selected setting on the spa panel.



Heating mode only

Heats the spa water.



Cooling mode only

Cools the water in the SPA