

















## CUBE +





- $\mathbf{W}^{\!\scriptscriptstyle{+}}$  ideal for SPAS and small pool
- **W**<sup>+</sup> R32 ecological gas
- **W**<sup>+</sup> LED controller
- W⁺ Bluetooth connection possible
- **W**<sup>+</sup> Smart defrosting

- **\**\\<sup>+</sup> CE certification
- **W**<sup>+</sup> Complies with FPP standards
- **W**<sup>+</sup> Compliance with environmental standards
- **\\**⁺ Plug & Play







## **SPECIFICATIONS**

PRODUCT	CUBE 3+	CUBE 4 <sup>+</sup>	CUBE 5 <sup>+</sup>
Basin capacity (max.)	15 m³	20 m³	25 m³
Heating power *	3 kW	4 kW	5 kW
Consumption *	0.62 kW	0.80 kW	0.98 kW
COP *	4.84	5.00	5.10
Heating power **	2 kW	2.70 kW	3.30 kW
Consumption **	0.56 kW	0.73 kW	0.89 kW
COP **	3.57	3.69	3.70
Power	230V~/50 Hz	230V~/50 Hz	230V~/50 Hz
Gas	R32	R32	R32
Туре	ABS	ABS	ABS
Fan direction	Horizontal	Horizontal	Horizontal
Fan rotation speed	800 T/min	800 T/min	800 T/min
Acoustic power at 1 m	48 dB(A)	49 dB(A)	50 dB(A)
Fitting diameter	ø32 mm	ø32 mm	ø32 mm
Unit size (l*L*h)	420 * 350 * 380 mm	420 * 350 * 380 mm	420 * 350 * 380 mm
Box size (I/L/h) (I*L*h)	450 * 420 * 400 mm	450 * 420 * 400 mm	450 * 420 * 400 mm
Equipment	Manual, winterization plug, electrical cable and connectors		
Controller	Remote control via App & Bluetooth connection possibility		
4-way valve	Yes	Yes	Yes
Operating range	-5°C ~ 43°C	-5°C ~ 43°C	-5°C ~ 43°C
Mode	Heating	Heating	Heating
Warranty all parts	2 years	2 years	2 years

<sup>\*</sup>Test carried out at 27°C air temperature with the same temperature and water flow rate difference obtained at 15°C.

## **ACCESSORIES**

- Hydraulic connectors - User manual

<sup>\*\*</sup>Test carried out at 15°C air temperature with a water inlet at 26°C and a water outlet at 28°C to define the water flow rate, heating capacity and consumption, according to FPP standards. Cube 3+ and 4+ are only available as imports and Cube 5+ from stock.